

BEPD 70L



Description

- BEPD 70L is a mixture of 2-Butyl-2-Ethyl-1,3-Propanediol (BEPD), Neopentyl Glycol and water
- Clear and colourless liquid at room temperature
- Diol containing primary hydroxyl groups

Applications

- Saturated polyesters for powder coatings, can and coil coatings and other stoving enamels
- High-solids coatings
- Unsaturated polyesters
- Short oil alkyds, both solvent- and waterborne
- Polyester polyols

Delivery forms

- Steel drums 195 kg, 780 kg/pallet
- Bulk

Storage

- Storage at room temperature is recommended. Storage at lower temperature can result in solidification of the product.

Handling

- All drums should be used in their entirety or agitated before use

Sales specification

BEPD content, % ¹	70 ± 1
Neopentyl glycol content, % ¹	25 ± 1
Water content, % ²	5 ± 1

BEPD approved according to BEPD product data sheet.

Neopentyl Glycol approved according to Neopentyl Glycol product data sheet

Analytical Method

¹ PO 130-1 (GC), ² PO 109-2 (ASTM E 1064-92)

Analytical methods are available on request

CAS no.: 115-84-4, 126-30-7

EC (EINECS) no.: 204-111-7, 204-781-0

HS no.: 3824 90

Valid from: May 1, 2002/c

Supersedes: January 14, 1999